

APPENDIX 3A
PHOTOS OF ROCK CORES

Phase 2 – Cacouna Energy, Gros Cacouna, Quebec

BH-4 : 0.8 – 17.5 m



Sandwell

ÉNERGIE
cacouna
ENERGY

J JOURNEAUX, BÉDARD
6 assoc. inc.

S-05-1743-2, Jan. 2006



27.4m -
Polished
surfaces at
right angle
with slicken
sides

Two smooth joint surfaces with slicken sides



Shaley zone between 31.7m and 32.1m with several smooth tight fractures with slickensides



Sandwell

ÉNERGIE
CAPOINE
ÉNERGIE

JB JOURNEAUX, BÉDARD
Énergie

Phase 2 – Cacouna Energy, Gros Cacouna, Quebec

BH-4 : 35.5 – 52.4 m



Sandwell

ÉNERGIE
cacouna
ENERGY

JB JOURNEAUX, BÉDARD
& assoc. inc.

S-05-1743-2, Jan. 2006

Phase 2 – Cacouna Energy, Gros Cacouna, Quebec

BH-4 : 52.4 – 65.6 m

Grout used to seal hole and prevent water loss.



Sandwell

S-05-1743-2, April 2006

ÉNERGIE
cacouna
ENERGY

JB JOURNEAUX, BÉDARD
& assoc. inc.

Phase 3 – Cacouna Energy, Gros Cacouna, Quebec

BH-5 : 0.3 – 16.5 m



Sandwell

ÉNERGIE
cacouna
ENERGY

JB JOURNEAUX, BÉDARD
& assoc. inc.

S-05-1743-3, Feb. 2006

Phase 3 – Cacouna Energy, Gros Cacouna, Quebec

BH-6 : 0.4 – 16.8 m



S-05-1743-3, Feb. 2006

Sandwell

Energy
cacouna
ENERGY

JOURNEAUX, BÉDARD
Associés

Phase 2 – Cacouna Energy, Gros Cacouna, Quebec

BH-7 : 0.4 – 11.0 m



Sandwell

ÉNERGIE
cacouna
ENERGY

JB JOURNEAUX, BÉDARD
& assoc. inc.

S-05-1743-3, Feb. 2006

Phase 3 – BH-7 : 11.0 – 30.8 m

